TSC03052



Organic Peroxides Storage

Standard Features

- Stainless steel pin continuous hinging for strength and reliability
- Strong fully adjustable shelving perforated for free air movement, 100mm adjustment increments
- High capacity liquid tight sump to contain spills
- State of the art powder coat finish for high durability and performance
- Built in flash arrestors and vent openings [for mechanical ventilation systems]
- · Distinct safety signs and directions
- Shipped on it's own purpose built individual and disposable skid with quality protection foam and wrapping ensuring arrival in perfect condition ready for use

For more info email to sales@trade-sales.com.au

or call 1800 999 521



SPECIFICATIONS

| | imension | s [mm] | |
|----------|----------|--------|-------|
| | Height | Width | Depth |
| External | 800 | 500 | 450 |
| Internal | 553 | 418 | 370 |

| M | Maximum Capacity | | |
|--------|------------------|-----|------|
| Litres | 4L | 20L | 205L |
| 23 | 3 | 1 | 0 |

| Weig | jht [l | kg] |
|------|--------|-----|
| (| 33 | |
| | | |
| Sh | elves | |

NO SMOKING
NO IGNITION SOURCES
WITHIN 3 METRES

ORGANIC
PEROXIDE
5.2

MAXIMUM CAPACITY 30 LITRES

© Copyright Tradesales, 2014

www.trade-sales.com.au

TSC10052



Organic Peroxides Storage



Standard Features

- Stainless steel pin continuous hinging for strength and reliability
- Strong fully adjustable shelving perforated for free air movement, 100mm adjustment increments
- High capacity liquid tight sump to contain spills
- State of the art powder coat finish for high durability and performance
- Patented sequentially closing and latching doors with smooth and gentle action for maximum safety and reliability
- Built in flash arrestors and vent openings [for mechanical ventilation systems]
- Distinct safety signs and directions
- Fully compliant with Australian Standards (AS1940-2004)
- Shipped on it's own purpose built individual and disposable skid with quality protection foam and wrapping ensuring arrival in perfect condition ready for use





SPECIFICATIONS

| D | imension | s [mm] | |
|----------|----------|--------|-------|
| | Height | Width | Depth |
| External | 800 | 920 | 615 |
| Internal | 553 | 838 | 535 |
| | | | |

| M | aximum (| Capacity | |
|--------|----------|----------|------|
| Litres | 4L | 20L | 205L |
| 100 | 24 | 3 | 0 |

| Weight [kg] |
|--------------------------------|
| 65 |
| |
| Shelves (including base level) |
| 2 |



For more info email to sales@trade-sales.com.au or call 1800 999 521



Organic Peroxides Storage



Standard Features

- Stainless steel pin continuous hinging for strength and reliability
- Strong fully adjustable shelving perforated for free air movement, 100mm adjustment increments
- High capacity liquid tight sump to contain spills
- State of the art powder coat finish for high durability and performance
- Patented sequentially closing and latching doors with smooth and gentle action for maximum safety and reliability
- Built in flash arrestors and vent openings [for mechanical ventilation systems]
- · Distinct safety signs and directions
- Fully compliant with Australian Standards (AS1940-2004)
- Shipped on it's own purpose built individual and disposable skid with quality protection foam and wrapping ensuring arrival in perfect condition ready for use

SPECIFICATIONS

| D | imension | s [mm] | |
|----------|----------|--------|-------|
| | Height | Width | Depth |
| External | 1220 | 1100 | 450 |
| Internal | 973 | 1018 | 370 |
| | | | |

| M | aximum (| Capacity | |
|--------|----------|----------|------|
| Litres | 4L | 20L | 205L |
| 160 | 40 | 6 | 0 |

| Weight [kg] |
|-----------------------------------|
| 78 |
| |
| Shelves (including base level) |
| 2 |

| NO SMOKING NO IGNITION SOURCES WITHIN 3 METRES | 1 | |
|--|----------------------------|---|
| | ONGANIC PEROXIDE 5.2 | > |
| | | |
| MARKING LANCON IN LOSES | | |

For more info email to sales@trade-sales.com.au or call 1800 999 521